

# TECHNICAL DATA

## SILKOLENE CHAIN LUBE

#### Synthetic technology motorcycle chain lubricant

#### **Description**

An advanced synthetic technology chain lubricant specially designed for high performance motorcycle chains, resistant to high speed fling off and providing outstanding wear protection. Silkolene Chain Lube effectively penetrates the inner rollers and pins, seals the chain to combat the ingress of water and other contaminants thus increasing chain and sprocket life. Silkolene Chain Lubricant is quick drying, forms a strong thin oil film and provides good corrosion protection.

Suitable for all chains including "O", "X" and Z ring types.

### **Application**

- Ensure chain is clean and dry prior to applying SILKOLENE CHAIN LUBE
- Fuchs Silkolene strongly recommends the use of SILKOLENE BRAKE AND CHAIN CLEANER prior to use
- Shake can well before application
- Apply sparingly to the whole length of the inside of a clean warm chain
- Leave for (time period) before use
- Wipe away excess
- Following application, invert the can and spray for a few seconds to avoid clogging the nozzle

### Advantages / Benefits

- · Good antiwear and shock loading performance
- Good resistance to high speed fling off
- · Resistant to water wash off
- Penetrates and evaporates quickly with excellent film forming properties
- Thin film formation resists dirt adhesion
- Good corrosion protection

March 2015 GDUK Page 1 of 1

#### **FUCHS LUBRICANTS (UK) PLC**

New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU Tel: +44 (0)1782 203 700

Email: contact-uk@fuchs-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.