

## SILKOLENE COMP 2

### Synthetic ester based pre-mix and injector 2-Stroke engine oil

#### Description

SILKOLENE COMP 2 is an advanced synthetic, low smoke, low ash 2-stroke engine oil formulated for 2-stroke engines fitted to both on and off road machines. SILKOLENE COMP 2 reduces engine wear, prevents piston seizure, ring sticking, plug fouling and exhaust port blockage. The advance formula also helps reduce friction, releasing hidden power and also ensures long-term performance retention. SILKOLENE COMP 2 is an environmentally friendly low-smoke lubricant which also gives outstanding reliability.

#### Application

SILKOLENE COMP 2 is recommended for many modern 2-stroke power units including road, off-road and scooters. SILKOLENE COMP 2 is recommended for both air and liquid cooled engines and can be used as either a pre-mix or with an injector system.

SILKOLENE COMP 2 is generally recommended for use at ratio of between 2 - 3% however users are advised to always follow engine manufacturers' recommendations for fuel / oil ratio

SILKOLENE COMP 2 should not be mixed with other oils, but is compatible with all leaded and unleaded fuels.

#### Advantages / Benefits

- Freedom from ring stick and deposit formation
- Prevents spark plug fouling and misfire
- Maximum power release
- Minimum engine wear
- Low ash blend to combat pre-ignition and maintain power output and fuel economy
- Low smoke performance for environmental acceptability

#### Specifications / Approvals

- |        |         |
|--------|---------|
| • JASO | FC / FD |
| • API  | TC      |
| • ISO  | L-EGD   |

**Typical Data: SILKOLENE COMP 2**

Characteristics	Test Method	Unit	Result
Specific Gravity at 15°C	IP160		0.873
Kinematic Viscosity at 40°C	IP71	mm <sup>2</sup> /s	71.0
Kinematic Viscosity at 100°C	IP71	mm <sup>2</sup> /s	10.3
Viscosity Index (VI)	IP226		130