

TECHNICAL DATA

SILKOLENE PRO 4 ENERGY 10W-30

Ultra high performance 4T motorcycle engine oil developed in cooperation with a major Japanese motorcycle manufacturer.

Description

SILKOLENE PRO 4 ENERGY 10W-30 uses an optimised formulation for both improved fuel economy and engine performance.

SILKOLENE PRO 4 ENERGY 10W-30 has balanced frictional properties for enhanced clutch control and proven high levels of engine and gear box wear protection.

Application

SILKOLENE PRO 4 ENERGY 10W-30 ensures rapid oil circulation on cold start, excellent lubrication under all conditions, and superior wet clutch performance.

Always consult engine manufacturers' handbook for SAE grade recommendations.

Specifications/Approvals

• API SG, SH & SJ

• JASO approved MA

Advantages / Benefits

- Advanced surface chemistry provides vital protection to pistons and bores, cam lobes and bearings, even during cold start
- High detergency formula is designed to keep engine internals clean and thereby maintain optimum engine efficiency and reliability
- The use of ultra-high performance base oils reduces volatility and provides reduced oil consumption
- Independent dynamometer testing showed engine peak BHP improvements of up to 6% compared to a range of 5W/40 and 10W/40 motorcycle oils
- Testing also showed fuel consumption benefits of on average 10%, compared to the same grades, providing greater power from the engine and improved MPG

FUCHS LUBRICANTS (UK) PLC

New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU

Tel: +44 (0)1782 203 700 Email: contact-uk@fuchs-oil.com While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.



TECHNICAL DATA

Typical Data: SILKOLENE PRO 4 ENERGY 10W-30

Characteristics	Test Method	Unit		
SAE Rating			10W-30	
Colour	Visual		Amber	
Specific Gravity at 15°C	IP160		0.854	
Kinematic Viscosity at 40°C	IP71	mm²/s	66.2	
Kinematic Viscosity at 100°C	IP71	mm²/s	10.8	
Viscosity Index (VI)	IP226		154	
Flash Point (Open Cup)	IP36	°С	248	
Cold Crank Viscosity	ASTM D5293	сР	4000	

FUCHS LUBRICANTS (UK) PLC

New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU Tel: +44 (0)1782 203 700

Email: contact-uk@fuchs-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.