

## TECHNICAL DATA

## **SILKOLENE SCOOT SPORT 4 5W-40**

#### **Description**

SILKOLENE SCOOT SPORT 4 5W-40 is specifically designed for modern high performance Scooters and offers excellent stay in grade performance over a wide temperature range.

Utilising high performance base fluids and additives SILKOLENE SCOOT SPORT 4 5W-40 offers outstanding anti-corrosion and anti-wear characteristics, low evaporation, extends exhaust system life and ensure low oil consumption.

#### **Application**

FUCHS SILKOLENE SCOOT SPORT 4 5W-40 is specifically designed for use in modern, high performance 4-stroke scooters and mopeds.

#### Specifications/Approvals

API SG, SH & SJ

JASO MA & MA2

#### **Advantages / Benefits**

- Superior stay-in-grade performance ensures full protection throughout the service life of the oil
- Low volatility reduces emissions, extends exhaust system life and ensures low oil consumption
- Viscosity characteristics ensure fuel efficient operation and easy starting in both summer & winter conditions
- Excellent anti-wear and anti-corrosion properties reduce friction thus promoting performance retention and long engine life

FUCHS LUBRICANTS (UK) PLC

New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU Tel: +44 (0)1782 203 700

Email: contact-uk@fuchs-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.



# TECHNICAL DATA

### Typical Data: SILKOLENE SCOOT SPORT 4 5W-40

Characteristics	Unit		Test Method
Kinematic Viscosity at 100°C at 40°C	mm²/s mm²/s	13.9 84.5	IP71
Viscosity Index (VI)		162	IP226
SAE Rating		5W-40	
Pour point	°C	-34	IP15
Flash Point (Closed Cup)	°C	190	IP34
Specific Gravity at 15°C		0.860	IP160

**FUCHS LUBRICANTS (UK) PLC** 

New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU Tel: +44 (0)1782 203 700

Email: contact-uk@fuchs-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.