

SILKOLENE SCOOTER GEAR OIL 80W-90

Advanced transmission gear oil

Description

SILKOLENE SCOOTER GEAR OIL 80W-90 is a high quality advanced gear oil based on highly refined mineral base oils and a high performance additive system providing outstanding transmission and gear protection over a wide range of operating conditions.

SILKOLENE SCOOTER GEAR OIL 80W-90 is packed in an easy-to-use one-shot 125ml tube, making it easy to use and minimising waste.

Application

FUCHS SILKOLENE SCOOTER GEAR OIL 80W-90 has been formulated specifically for use in scooters and mopeds and is suitable for use in all scooters where an API GL-4 SAE 90, 85W-90 or 80W-90 is specified.

Specifications/Approvals

- API GL4

Advantages / Benefits

- Excellent wear protection
- Multigrade viscosity gives good performance over a wide temperature range
- Easy to use one-shot tube
- Gives outstanding lubrication performance and efficient power transmission, ensuring total reliability and minimal transmission noise

Typical Data: SILKOLENE SCOOTER GEAR OIL 80W-90

Characteristics	Unit		Test Method
Kinematic Viscosity			IP71
at 100°C	mm ² /s	15.0	
at 40°C	mm ² /s	151.2	
Viscosity Index (VI)		99	IP226
Pour point	°C	-28	IP15
SAE Rating - Gearbox		80W-90	
SAE Rating - Engine		20W-50	
Specific gravity at 15°C		0.899	IP160