

## SILKOLENE V-TWIN RANGE

A dedicated range of high performance motorcycle lubricants formulated for V-Twin designs

### Description

SILKOLENE V-TWIN 20W-50 is formulated on highly refined mineral base oils and performance additives specifically for Harley Davidson and Metric V-Twins where a 20W-50 is specified.

SILKOLENE V-TWIN 20W-50 provides high levels of engine cleanliness and protects engine components from wear and corrosion.

SILKOLENE V-TWIN 80W-90 is an extreme pressure gear oil designed again for Harley Davidson and Metric V-Twins and provides outstanding wear and gear protection over a wide operating temperature range and in all riding conditions.

### Specifications/Approvals

#### SILKOLENE V-TWIN 20W-50

- API CF / SG / SH / SJ
- JASO MA & MA2

#### SILKOLENE V-TWIN 80W-90

- API GL5

### Advantages / Benefits

#### SILKOLENE V-TWIN 20W-50

- Excellent wear, corrosion and oxidation protection
- Protects over a wide range of operating temperatures and conditions
- Promotes a high level of engine cleanliness
- Keep critical engine components operating at maximum efficiency

#### SILKOLENE V-TWIN 80W-90

- Excellent gear protection even under shock loading
- Good oxidation stability and corrosion protection
- Ensures smooth gear change throughout the entire rev range

**Typical Data: SILKOLENE V-TWIN RANGE**

Characteristics	Test Method	Unit	Results	
			20W-50	80W-90
<b>SILKOLENE V-TWIN ...</b>			<b>20W-50</b>	<b>80W-90</b>
Colour	Visual		Dark amber	Dark amber
Specific Gravity at 15°C	IP160		0.891	0.901
Kinematic Viscosity at 40°C	IP71	mm <sup>2</sup> /s	168.4	181.7
Kinematic Viscosity at 100°C	IP71	mm <sup>2</sup> /s	19.1	16.9
Viscosity Index (VI)	IP226		129	98
Flash Point	IP34	°C	200	230
Pour point	IP15	°C	-25	-30